



Master™ Leather Fillet and Fillet Cement

Master™ Leather Fillet

MASTER Leather Fillet is made from the highest grades of leather and shaped to exact size. The leather is pliable and has thin straight edges that blend readily with the surface of the pattern.

Backs of the strips are slightly notched to permit shaping to the desired radius and contour.

MASTER Leather Fillet is easily applied by the use of MASTER Fillet Cement and the proper size MASTER Steel Fillet Tool (Page 42).



To order please specify catalog number and quantity desired.

Strips are Approximately 44" Long

Size	Radius (Inches)	Width of Flat Face (Inches)	Feet Per Bundle	Catalog Number	Size	Radius (Inches)	Width of Flat Face (Inches)	Feet Per Bundle	Catalog Number
1/2	1/32	1/16	100	850-005	8	1/2	3/4	100	850-08
1	1/16	3/32	100	850-01	10	5/8	21/32	100	850-10
1-1/2	3/32	1/8	100	850-015	12	3/4	1-5/32	100	850-12
2	1/8	3/16	100	850-02	14	7/8	1-3/8	50	850-14
2-1/2	5/32	1/4	100	850-025	16	1	1-9/16	50	850-16
3	3/16	5/16	100	850-03	20	1-1/4	2	50	850-20
4	1/4	3/8	100	850-04	24	1-1/2	2-3/8	50	850-24
5	5/16	1/2	100	850-05	28	1-3/4	2-1/2	50	850-28
6	3/8	9/16	100	850-06	32	2	2-3/4	50	850-32
7	7/16	21/32	100	850-07					

Master™ Fillet Cement

For Attaching Leather Fillets

MASTER Fillet Cement is formulated for use with leather fillets. When the cement dries, sand will not stick to the edges of the fillet. It is fast drying and is used in preference to white glue. The cement is impervious to heat up to 175°F, and will not curl the edges of leather fillets.

Use MASTER Universal Adhesive Solvent for thinning and removing excess MASTER Fillet Cement.



To order Fillet Cement, please specify catalog number and quantity desired.

Description	Size	Catalog Number
MASTER Fillet Cement	1 Quart	920-FC1Q